

PilotOEM

Diode Laser Controller
Low Noise Laser Current
High Temperature Stability

Electronic Systems & Devices



Product Features

- 500mA / 3000mA LD current source with forward voltage measurement
- Const current or const power mode
- 16 W / 32 W TEC control
- Various laser protection features
- External power stage
- RS232 remote interface
- Optional USB, Ethernet remote interface



Specifications

Laser Current Source		Temperature Control	
PC5000EM Drive Current Output		TEC Output	
Output Current Range	0-500mA	Output Type	Constant current source bridge
Setpoint Resolution	0.1mA	Compliance Voltage	8V
Setpoint Accuracy	±0.1%	Maximum Output Current	-2A to 2A / -4A to 4A
Compliance Voltage	0-7V adjustable		
		Sensor	
PC3000OEM Drive Current Output		Temperature Sensor	Thermistor (PT1000)
Output Current Range	0-3000mA		IC Temp Sensor AD590
Setpoint Resolution	0.1mA	Temperature Control Range	-5°C to 30°C
Setpoint Accuracy	±0.1%	Setpoint Resolution	0.1°C
Compliance Voltage	0-7V adjustable		
		Common Data	
Photodiode Feedback		Dimension (WxHxD)	170 x 140 x 42 mm
Photodiode Current Range	2-2000uA	Line Voltage	110V .. 230V
Type	Diff. 100R Input	Line Frequency	47 .. 63Hz
		Operating Temperature	0°C .. 40°C

Please contact us

Sacher Lasertechnik
GmbH
R. Breitscheid Str. 1-5
D-35037 Marburg/Lahn
Germany
Tel.: +49 6421 305 - 0
Fax: +49 6421 305299

Sacher Lasertechnik
LLC
5765 Equador Way
Buena Park, CA90620
U. S. A.
Tel.: 1-800-352-3639
Fax: 1-714-670-7662

Email: contact@sacher.de
Web: <http://www.sacher.de>

