

OPP-AO Series

OPTICAL PULSE PICKER

PriTel's OPP Series of Optical Pulse Pickers are designed for selecting a single optical pulse from an optical pulse train.

The OPP uses an Acousto-Optic Modulator (AOM) that is driven by an electrical signal synchronized to the input optical pulse train.

A countdown pre-scaler in the driver circuit selects the output pulse rate and a preset delay controls the phase between the electrical and optical inputs. The OPP produces optical pulse trains with a low insertion loss and excellent rejection (>40 dB) of the input frequency.



Specifications

Model	OPP-AO-1550
Operating Wavelength	1550 nm band
Insertion Loss	< 6 dB (for picked pulse)
Input Pulse Repetition Rate	<= 40 MHz
Output pulse repetition rate	Input divided by 2^N (fixed or adjustable)
Picking Ratio	1 in 2^N (fixed or adjustable)
Gating window duration	< Input period
Extinction Ratio (ER)	> 40 dB (>20 dB for immediate neighboring blocked pulse)
Synchronization to External Clock	Yes
Electrical Sync Output	Yes
Input/Output fibers	PM – Key aligned to slow axis
Maximum input power	100 mW
Environmental	
Operating temperature	+10 to 40°C
Storage temperature	-20 to 50°C
Electrical/ Mechanical	
Operating Voltage	85-264 VAC at 47-63 Hz
Power consumption	<100 W
Dimensions	10 cm x 26 cm x 36 cm, 8 Kg



PriTel, Inc.
P.O. Box 4025,
Naperville, IL 60567-4025, USA
Ph: +1-630-983-2200, Fx: +1-630-983-2260
E-mail: PriTel@PriTel.com
, Internet: www.PriTel.com

Typical Performance of Optical Pulse Picker

